



Waterside Model Club

Tamiya TT01E Truck Rules

Truck must be a TT01E Tamiya kit using the parts contained within the kit, except for the permitted options listed below:

Full bearing kit

Oil filled shocks (any brand)

61t Spur Gear (standard out of the box)

Steel / hardened 19t Pinion (kit pinion is 19t and can be used if preferred, the hardened option is purely for longevity purposes).

2S Lipo full size or shorty or 7.4 NIMH

One of the following ESCs:

- Tamiya TBLE-02 (with Lipo alarm if using Lipo cella)
- Hobbywing 1060/1080 set to Lipo (if using Lipo cells)
- Hobbywing 1080 set to Lipo (if using Lipo cells)

Tamiya Torque Tuned motor or CoreRC 21t sealed silver can motor. Cranking to advance the timing is not permitted.

Motor fan

Any steering servo

M-chassis wheel and Tamiya truck tyre or RIDE pre glued 1/10 10 Spoke wheel Part No RI-26073 (not to be confused with the similar but larger diameter Ride TR-09 RI-36086 which **are not permitted**)

Front and rear differentials capable of diff action (i.e. not locked)

Front Universal Joint driveshafts

Alloy centre shaft and cups

Steering Turnbuckles

Alloy Motor Mount

Any commercially available truck racing body

Minimum ride height 5mm

Minimum weight 1500 grams

Anything not listed above must be left as per the TT01E kit

Note, these are optional upgrades, you can run the truck as it comes out of the box with one of the detailed ESC and motor combinations to get you started.

Stuart & Romano

Last Updated: - 01/09/2025